

MWIR Continuous zoom – Commercial off the shelf lens

JUNO

MWIR 18-275mm F/5.5 Continuous zoom Lens
for 640 x 512 x 15µ cooled detectors



FEATURES / APPLICATIONS / CAPABILITIES

- Ultra Compact and light lens, Weighs ONLY 220g.
- "ZERO BORESIGHT" design for high accuracy demanding applications
- Focus is maintained through the entire zoom & temperature range

	HFOV for Wide (18mm)				HFOV for Narrow (275mm)			
	640x512	1024x768	1280x1024	IFOV (mrad)	640x512	1024x768	1280x1024	IFOV (mrad)
10u	20.2°			0.032	1.3°			0.0021
12u	24.1°			0.038	1.6°			0.0025
15u	29.9°			0.048	2°			0.0031

PARAMETER		VALUE	NOTES
Main	Sub		

🕒 OPTICAL

Focal Length / F#		18 - 275 mm F/5.5	
Detector (FPA) type / size		Up to 640 x 512 x 15µ	
Working Spectral Range		3 – 5µ	
Optical Coatings	All internal surfaces	High efficiency AR coating	
	Front surface	High durability AR coating	DLC is available upon request
CSH		19-22mm	

⚙️ MECHANICAL

Focus / Zoom mechanism		Motorized	
Focus range		10m /30m – Infinity	For WOFV / NFOV accordingly
Through zoom boresight		≤ 0.075mm radius at the focal plane	
NFOV boresight retention		≤ 0.03mm radius at the focal plane	
Total Weight		220gr	
Ext. Dimensions ø x length (mm)		63.5x71.3	

💡 ELECTRICAL

Power Input		12VDC, 1.0 A	
Communication Protocol		RS-422/232 Full Duplex	

🌍 ENVIRONMENTAL

Operating/Storage Temperature		-25°C to +55°C / -40°C to +70°C	
Shock and Vibrations		Per applicable standard	
Front lens sealing		IP66	IP67 By request

*All values are nominal: to within ±5%

